



Quantum Profile Systems Ltd Salmon Fields, Royton Oldham, OL2 6JG, UK

tel: +44 (0) 161 627 4222 fax: +44 (0) 161 627 4333

info@quantumflooring.co.uk www.quantumflooring.co.uk

## **CLEANING GUIDELINES: STAIR NOSINGS**

DO NOT USE SOLVENTS!

DO NOT TRAFFIC WHILST WET!

MAKE SURE ALL CLEANING SOLUTIONS ARE REMOVED.

# MATERIAL TYPE – ALUMINIUM STAIR NOSING CARRIER: S-Range, H-Range, Z-Range Q-Range

- Clean aluminium carrier with a mild detergent solution\* then polish with a clean dry cloth. If required use a scouring pad to remove any ingrained dirt.
- Dry off if necessary with lint free cloth.

#### MATERIAL TYPE - PVC CARRIER: H-Range, Q-Range

- Clean tread with a mild detergent solution using a scouring pad to remove any heavy soiling.
- Dry off if necessary with lint free cloth.

# MATERIAL TYPE - PVC TREAD: S-Range, H-Range, Z-Range Q-Range

- Both infill and nosing should be cleaned with a mild detergent solution\*.
- Dry off if necessary with lint free cloth.

\*Please consult recommended manufacturers guides for cleaning products.

# MATERIAL TYPE - ECOGLO TREAD: S-Range, H-Range

#### 1 Overview

- Regular cleaning to remove built up dirt and objects will ensure the Ecoglo products will continue performing to expectation.
- The photoluminescence will continue performing even after UV exposure or exposure to moisture.

#### 2 Floor mounted Products

- Vacuuming or brushing with a stiff bristle head (dry or wet) is often enough to keep the strips clean. The glowing strip can also be wiped clean with a (dry or wet) sponge or cloth.
- High-pressure water (but not steam cleaning) can also be used. Observation will determine if cleaning is required however a regular clean every 4 to 6 weeks or after particularly heavy use should ensure correct performance.

NOTE: Do not use highly alkaline or acidic cleaning agents. The pH of the cleaning agents should be between pH 5 and pH 12. If cleaning agents are applied at more than pH 10, the Ecoglo material should be rinsed with pH neutral (pH 6 to pH 8) solution afterwards.

## Regular cleaning:

The frequency of regular cleaning method will depend on the amount of traffic, soiling levels, desired appearance, and hygiene standards.

If you require any further details please email technical@quantum-ps.co.uk

Quantum Profile Systems Ltd / Jul 2016



QPSL Group strives for continuous improvement in our environmental, health and safety management systems and in the environmental quality of our products, processes, and services.